

S524

Corner Radius End Mill



1.7 1.8

d ₁ R mm	r ± _{0.01} mm	d ₂ R _{h6} mm	l ₂ mm	l ₁ mm	z	l ₃ mm	d ₃ R mm	e-code	GBP
3.00	0.30	6	5	75	4	30.0	2.8	S5243.0XR0.3	75,50
4.00	0.30	6	8	75	4	32.0	3.7	S5244.0XR0.3	82,20
4.00	0.50	6	8	75	4	32.0	3.7	S5244.0XR0.5	82,20
5.00	0.30	6	9	75	4	32.0	4.6	S5245.0XR0.3	83,90
5.00	0.50	6	9	75	4	32.0	4.6	S5245.0XR0.5	83,90
6.00	0.30	6	10	75	4	40.0	5.5	S5246.0XR0.3	83,90
6.00	0.50	6	10	75	4	40.0	5.5	S5246.0XR0.5	83,90
6.00	1.00	6	10	75	4	40.0	5.5	S5246.0XR1.0	83,90
8.00	0.30	8	12	75	4	40.0	7.4	S5248.0XR0.3	117,00
8.00	0.50	8	12	75	4	40.0	7.4	S5248.0XR0.5	117,00
8.00	1.00	8	12	75	4	40.0	7.4	S5248.0XR1.0	117,00
10.00	0.50	10	14	75	4	40.0	9.2	S52410.0XR0.5	155,00
10.00	1.00	10	14	75	4	40.0	9.2	S52410.0XR1.0	155,00
10.00	2.00	10	14	75	4	40.0	9.2	S52410.0XR2.0	155,00
12.00	0.50	12	16	100	4	60.0	11.0	S52412.0XR0.5	214,00
12.00	1.00	12	16	100	4	60.0	11.0	S52412.0XR1.0	214,00
12.00	2.00	12	16	100	4	60.0	11.0	S52412.0XR2.0	214,00
16.00	0.50	16	22	125	4	85.0	15.0	S52416.0XR0.5	352,00
16.00	1.00	16	22	125	4	85.0	15.0	S52416.0XR1.0	352,00
16.00	2.00	16	22	125	4	85.0	15.0	S52416.0XR2.0	352,00
16.00	3.00	16	22	125	4	85.0	15.0	S52416.0XR3.0	352,00